



PHONTECH Communication Systems


MPA 1600 PUBLIC ADDRESS SYSTEM



www.jotron.com

► MPA 1600 PUBLIC ADDRESS SYSTEM

The MPA 1600 system is a marine and offshore Public Address system, especially designed to meet the requirements for PA/GA and entertainment distribution onboard ships and mobile offshore units. The system is in conformity to SOLAS, IMO and IEC regulations. Based on a modular design and flexible configuration, the system covers a wide range of installation complexities from small single loop to fully duplicated systems utilizing total redundancy.



SYSTEM

- Cabinets and racks with integrated ships cable termination modules
- Flexible system configuration meets most specifications.
- Prepared for seamless amplifier or full duplication (redundancy)
- Up to 6 zones selectable in any configuration
- Up to 24 control units, full facility (MPA 1601/1603)
- Up to 2 emergency microphone inputs
- External paging facility (from ICS6200/PABX etc.)
- Interface to manual and/or automatic alarm generation
- 2 entertainment sources, free zone selection
- Signal processing
- Preselectable priority levels
- Unlimited amplifier expansion
- Facility for muting local loudspeaker during paging
- Override of entertainment volume-controls during paging
- Output for mute of external GA system
- Output for activation of external GA system
- Synchronisation of external GA tones
- Up to 8 different alarms w/priority (optional)
- Chime/"ding-dong" generator
- Alarm light signal activation (optional)
- Mute of external alarm facility (optional)

SPECIFICATIONS

- MPA 1600 and power amplifiers are 19" rack mounting
 - 16439MPA Cabinet 15U/19"
 - 18935MPA Cabinet 16U/19"
 - 18937MPA Cabinet 34U/19"
- Available options:
- MPA 1602 Entertainment module
 - EV-20R Message storage module
 - Amplifiers
 - Hot standby facility
 - Dual amplifier bank
- Dual power: 230VAC/230VAC or 230VAC/24VDC with automatic mains failure backup
 - Available amplifiers: 120W, 240W, 360W, 480W / 100V line
 - Related units: Relay unit 9000, volume controls
 - Signal lights, PA loudspeakers (100V line)
 - External paging input/output
 - Entertainment input
- MPA 1601 control unit, flush mounting
 - Noise cancelling gooseneck or hand microphone (optional)
 - Adjustable backlight
 - MPA 1601 dimension: H=144mm, w=144mm





Volume controls.



20W



60W

Microphone station 1176
single systemMicrophone station 1808
dual system

MPA 1600 is type approved by DNV, RINA, CCS, ABS and RMRS.



Agent/Distributor:



www.mackaymarine.com

marinesales@mackaymarine.com

+1 281 479 1515

service@mackaymarine.com

+1 281 478 6245

Jotron AS reserves the right to change the design and/or specifications at any time without prior notice. Reservations are also taken towards any general errors that may occur.

www.jotron.com

CONTACT INFORMATION

Jotron AS
P.O.Box 54
3281 Tjodalyng
Norway
Tel: +47 33 13 97 00
Fax: +47 33 12 67 80
sales@jotron.com

Jotron UK Ltd.
Crosland Park
Cramlington
NE23 1LA
United Kingdom
Tel: +44 (0) 1670 712000
Fax: +44 (0) 1670 590265
sales@jotron.com

Jotron Asia Pte. Ltd.
19 Loyang Way
Changi Logistics Centre
Rear Office Block 04-26
Singapore 508724
Tel: +65 65426350
Fax: +65 65429415
sales@jotron.com

Jotron USA, Inc.
10645 Richmond Avenue, Suite
170
Houston, TX 77042
USA
Tel: +1 713 268 1061
Fax: +1 713 268 1062
sales@jotron.com

v.F