

# AvL TECHNOLOGIES

## Model 1258 Mobile VSAT 1.2m Motorized Transportable Vehicle-Mount Antenna



- Unique Features**
- 1.2m AvL Engineered Composite Reflector
  - Zero Backlash AvL Cable Drive
  - Compact/Rugged Pol Gear Drive
  - “One-Button” Auto-Acquisition
- Standard Rx/Tx Feed Polarization Adjustment Standard Colorization**
- 2-Port Ku-Band Precision (standard Cross-Pol comp.)
  - Motorized Worm Gear Drive
  - AvL Metallic Gray (optional colors available)

### Mechanical

Az/EI Drive	Motorized AvL Zero Backlash Cable Drive (Patent Pending)
Polarization Drive System	Motorized Worm Gear Drive
Reflector Construction	1.2m Single Piece AvL Engineered Composite
Axis Travel	
Azimuth	400° (±200°)
Elevation	0-90° antenna boresight
Mechanical	
Electrical	Standard limits at 5° to 65° (CE Approval) or 0° to 90°
Polarization	±95°
Az/EI Speed	
Slewing/Deploying (typical)	2°/second
Peaking (typical)	0.2°/second
Motors	24 VDC Variable Speed, Constant Torque
RF Interface	
BUC/HPA Mounting	Feed Boom (maximum weight 15 lbs (6.7 kg))
Max dimensions for BUC mounting on Feed Boom	22 L x 13.8 W x 8.5 H inches (56 L x 35 W x 22 H cm)
Feed Tx	Flex waveguide from feed, WR75
Coax	Two Type F connectors at antenna base
Electrical Interface	One 25 ft. (8 m) cable with connectors to controller
Manual/Emergency Drive	Handcrank on Az, EI and Pol axes
Weight (approximate)	100 to 120 lbs. (46 to 55 kg) depending on options
Stowed Dimensions	70 L x 48 W x 15 H inches (178 L x 122 W x 38 H cm)
Time to Acquisition	Less than 10 minutes, 8 minutes typical
Mounting	Pallet for vehicle roof mounting

### Environmental

Wind – Survival	Deployed: 55 mph (105 kph); Stowed: 80 mph (129 kph)
Wind - Operational	45 mph (72 kph)
Pointing Loss in Wind (Ku RX):	
20 mph (32 kph)	0.5 dB typical
30 mph gusting to 45 mph (48 kph gusting to 72 kph)	1.4 dB typical
Temperature:	
Operational	-22° to 125° F (-30° to 52° C)
Survival	-40° to 140° F (-40° to 60° C)

# AvL TECHNOLOGIES

## Model 1258 Mobile VSAT 1.2m Motorized Transportable Vehicle-Mount Antenna

### RF/Electrical

Feed Type ▶	Std. 2-Port Precision Ku	
RF Parameter ▼	Receive	Transmit
Frequency Range (GHz)	10.95 - 12.75	13.75 - 14.50
Polarization Configuration	Linear orthogonal standard, optional co-pol	
Gain (mid-band) (dBi)	41.6	43.1
Beamwidth -3dB (Degrees)	1.5	1.2
-10 dB (Degrees)	2.7	2.2
Radiation Pattern Compliance	FCC §25.209, ITU-R S.580-6	
Antenna Noise Temperature	54° K @ 20° elevation	
Allowable Input Power Density		FCC: -14 dBw/4 kHz ITU: -0 dBw/4 kHz
VSWR	1.30:1	1.30:1
Cross-Polarization Isolation (dB)		
On Axis (minimum)	35	35
Off Axis (within pointing cone)	27	28
Feed Port Isolation	35	80

### Controller

#### Standard Controller

Standard Features	One button auto-acquisition of selected satellites, including peaking and optimization of cross pol. Internal movement detector and automatic stow. Certified for auto-commissioning on most satellite services.
Size	10 x 9 x 2.5 inch power supply
Input Power	28 VDC (190 W antenna running with max load)

### Available Options, Upgrades & Services

- Roof rack mounting kit (designed with interface for standard Thule Bar Kits: [www.thule.com](http://www.thule.com))
- Power supply (250 W) – 1RU with display/keypad, 120-240 VAC 50/60 Hz 4A peak
- Handheld controller (plugs into 1RU front panel) with 25' cable
- Add BUC/HPA Mounting (NOTE: minimum elevation may be restricted by these options)
- Optional Rotary Joint on Pol Axis with Flex W/G to BUC
- Upgrade to Custom RF/IF I/O cabling configurations available
- Custom Colorization (contact factory for available colors)
- Add Custom Logo on Reflector Face (1- or 2-Color; per AvL Logo Policy)
- Spare Parts Kit
- Lightweight antenna cowling



[www.mackaycomm.com](http://www.mackaycomm.com)

+1 919 850 3100  
[satserv@mackaycomm.com](mailto:satserv@mackaycomm.com)

Satellite PTT, Voice & Data  
 Equipment and Airtime